

DATASHEET

Fuelfix & Tanks2Go 0.5FF Self-Bunded Tank

Ideal for use in stand-by applications for refuelling smaller equipment, such as industrial heaters, small generators, lighting towers and more.



Movable

Full load lifting eyes, forklift pockets and internal baffles are designed to allow safe and easy handling of the tank full of fuel.

Stackable

Easily stackable design supports 2 high when full and 3 high when empty, reducing storage space requirements.

Accessible

Access manway for thorough maintenance and inspection. Removable inner tank for servicing and cleaning.

Efficient

Lockable cabinet secures equipment. Fuel ports can run up to 3 pieces of diesel-powered equipment.

Environment-Friendly

Secondary containment is compliant with AS1940 (2017). The tank design is compliant with UL142.

Gross Capacity: 500L	Height: 855 mm
Safe Fill: 474L	Length: 1,165 mm
Weight (Empty): 415 kg	Width: 1,165 mm
Weight (Full Tank): 889 kg	Design Standards: UL142, UN31A, UN1202
Australian Standards: AS1940 & AS1692	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

3" fill point; 2" fusible link fill port, 1" pump feed with flexible suction line, strainer and non-return valve, 1 engine feed and return port set, working vent, breather vent.

Optional Fittings

Complete transfer pump kits, water and particulate filter kits, fuel up to 2 feed and return blocks, fuel hose and quick couplers.