

Fuelfix & Tanks2Go

105FF Self-Bunded Tank

The Fuelfix Self-Bunded 105FF tank is designed to leverage the efficiencies of having large scale fuel storage capacity. Ideal for transportation depots, mining and construction on-site refuelling. It is perfect for manifolding to create a large singular storage facility to suit all storage volume needs.



Movable

This tank is easily transported using side-loaders, removing the need for cranes, EWP's and any related working at height risks when loading and unloading.

Secure and Efficient

Overfill protection supplied with mechanical shut-off and alarm. Free-to-air vent weather cap. Tank floor has fall-to-front for water collection and tank-top evacuation point. Front mounted security doors with container lock handles.

Accessible

Fixed ladder at front of tank and under tank visibility.

Environment-Friendly

Anti-syphon valve prevents fuel loss and possible contamination should a pipe or hose fail. Clip-on Pump Bay option available (refer [Clip-on Pump Bay Datasheet](#) for more details).

Gross Capacity: 104,000L	Height: 3,200 mm
Safe Fill: 100,200L	Length: 14,630 mm
Weight (Empty): 17,100 kg	Width: 2,500 mm
Weight (Full Tank): 101,268 kg	Design Standards: UL 142, ULCS601
Australian Standards: AS1940, AS1657, AS1692	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

3" fire safe ball valves, container corner castings, primary tank access manway, calibrated fluid level dipstick, statutory signage and interstitial space dip point. And an AS1940 compliant fill-point. Finished in white marine grade polyurethane paint.

Optional Packages

- HV/LV dispensing package
- Single or dual vehicle pump package (light to medium vehicles)
- Lubricant dispensing package
- Fuelfix fuel management system