

Fuelfix & Tanks2Go 4FF Self-Bunded Tank

Extend the run time of your diesel-powered equipment with the self-bunded 4FF tank. Increased efficiency with reduced expenses means maximized revenue.



Stackable

Easily stackable design supports 2 high when empty, reducing storage space requirements. (not rated to be stacked when full.)

Accessible

Access manway for thorough maintenance and inspection of the inner tank.

Efficient

Top mounted lockable spill containment box secures tank fill, dip point and interstitial dip point. Top mounted sockets can support two diesel suction lines and one return line. There is a 2" BSP port and a 1" BSP port to be used as required (generally as feed and return ports).

Environment-Friendly

Tank complies with UL142 design.

Gross Capacity: 4,500L	Height: 1,256 mm
Safe Fill: 4,000L	Length: 2,068 mm
Weight (Empty): 1,200 kg	Width: 2,262 mm
Weight (Full Tank): 4,560 kg	Design Standards: UL142
Australian Standards: AS1940, AS1692	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

2" fill point, 2" pump feed, 1" return port, breather vent (all BSP).

Optional Fittings

Complete transfer pump kits, water and particulate filter kits, fuel up to 2 feed and return blocks, generator hose kit with suction and return hoses fitted with quick couplers.