

DATASHEET

Fuelfix & Tanks2Go T2 Self-Bunded Tank

The Fuelfix & Tanks2Go T2 is the perfect solution to a wide range of mobile fuel storage needs, allowing for the direct supply to plant and equipment at any location. Compact, tough and reliable, the T2 transports with ease from building sites to mine sites.



Movable

The tank can be easily moved, by a suitable forklift, to ensure the safe and easy handling of the tank when empty.

Stackable

Easily stackable design when empty, reducing storage space requirements.

Accessible

Access manway for thorough maintenance and inspection of the primary tank.

Efficient

Lockable hatch secures the fill, dip and interstitial dip points of the tank. This tank is ideal for smaller fuel requirements such as generators or connecting to an electrical pump for product transfer.

Environment-Friendly

Self-bunded tank constructed to AS1692 and AS1940.

Capacity: 2,100L	Height: 1,369 mm
Safe Fill: 2,000L	Length: 900 mm
Weight (Empty): 1,100 kg	Width: 2,200 mm
Weight (Full Tank): 2,780 kg	Australian Standards: AS1940, AS1692

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

Vent pipe, dipstick, 50mm fill line, 50mm suction line, 25mm return ports, and pump suction spear.

Optional Equipment

- 240V, 24V or 12V dispensing pump with mechanical meter and 4m hose with auto shut-off nozzle
- Solar kit available on 12V pump option
- Generator hose kits