

Fuelfix & Tanks2Go T55 Self-Bunded Tank

Keep up with fuel demand and stay fully operational with our T55 fuel storage solution, which can be adapted to meet any requirement, while meeting all HSE standards.

Movable

Safe handling can be easily achieved using a crane or semi tilt-tray.

Accessible

Access manway for thorough maintenance and inspection of the primary tank.

Efficient

The front cowling area is self-bunded and can be fitted with a removable skid pump module or day tank.

Environment-Friendly

Self-bunded tank constructed to AS1692 and AS1940. The front cowling ensures that any spills that occur during tank filling or maintenance are securely contained within a bunded area.



Capacity: 54,200L	Height: 3,500 mm
Safe Fill: 52,600L	Length: 11,600 mm
Weight (Empty): 10,300 kg	Diameter: 2,780 mm
Weight (Full Tank): 54,484 kg	Australian Standards: AS1940, AS1692, AS1657

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

9 kg dry powder extinguisher, vent pipe and dipstick, 80mm fill line with mechanical overfill prevention valve, 50 mm suction line, 2" wet test port, audible overfill alarm and cowling light. Ladder, ladder cage (where applicable) and platform built to AS1657

Optional Equipment

- Various electric and diesel-powered dispensing and tanker unloading solutions to suit all applications
- Fuelfix fuel management system with optional tank gauging
- 1,000L or 2,000L generator day tank
- NMI approved meter