

# Fuelfix & Tanks2Go T70 Self-Bunded Tank

This tank forms an invaluable part of our hydrocarbon storage line-up. It is the perfect combination of capacity and size which can accept a full B-Double load thereby maximizing fuel purchasing power.



## Movable

Safe handling can be easily achieved using a crane.

## Accessible

Access manway for thorough maintenance and inspection of the primary tank.

## Efficient

The front cowling area is self-bunded and can be fitted with a removable skid pump module or day tank.

## Environment-Friendly

Self-bunded tank constructed to AS1692 and AS1940. The front cowling ensures any spills during tank fill or while performing maintenance are securely contained within the bunded area.

Capacity: <b>71,800L</b>	Height: <b>3,500 mm</b>
Safe Fill: <b>69,600L</b>	Length: <b>14,600 mm</b>
Weight (Empty): <b>13,100 kg</b>	Diameter: <b>2,774 mm</b>
Weight (Full Tank): <b>71,564 kg</b>	Australian Standards: <b>AS1940, AS1692</b>

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

## Standard Fittings

9 kg dry powder extinguisher, vent pipe and dipstick, 80 mm fill line with mechanical overfill prevention valve, 80 mm suction line with anti-syphon valve, audible overfill alarm, cowling light, ladder, ladder cage (where applicable) and platform built to AS1657

## Optional Equipment

- Various electric and diesel-powered dispensing and tanker unloading solutions to suit all applications
- Fuelfix fuel management system with optional tank gauging
- 1,000L generator day tank
- NMI approved meter