

DATASHEET

Fuelfix & Tanks2Go 1FF Self-Bunded Tank

A compact, transportable, double-walled fuel tank that can quickly and easily supply fuel where you need it, when you need it.

Movable

Full load lifting eyes, forklift pockets and internal baffles are designed to allow safe and easy handling of the tank full of fuel.

Stackable

Easily stackable design supports 2 high when full and 3 high when empty, reducing storage space requirements.

Efficient

Lockable hatch secures equipment. Fuel ports can run up to 3 pieces of equipment.

Environment-Friendly

Secondary containment is compliant with AS1940 (2017). The tank design is compliant with UL142.



Gross Capacity: 955L	Height: 1,306 mm
Safe Fill: 925L	Length: 1,135 mm
Weight (Empty): 710 kg	Width: 1,135 mm
Weight (Full Tank): 1,478 kg	Design Standards: UL142, ULC-S601-07
Australian Standards: AS1940 & AS1692	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

3" fill point, 6 x 25NB suction/return speared lines, 32NB suction line speared, roll over vent, breather pipe.

Optional Fittings

Complete transfer pump kits, water and particulate filter kits, Fuel hose and quick couplers.