

DATASHEET

# Fuelfix & Tanks2Go 10,000L Self-Bunded Tank

A low-set, double-walled tank designed for stationary storage. With quick and easy set-up and relocation, you can access fuel where you need it, when you need it.



## Movable

Forklift pockets are designed to allow safe and easy handling of the tank.

## Stackable

The easy stackable design reduces storage space requirements.

## Accessible

Access manway for thorough maintenance and inspection of inner tank.

## Efficient

Secure tanker fill point with 80nb full bore, fire-safe flanged ball valve and wafer style non-return valve. Includes a 3" AS1940 compliant overfill prevention valve with mechanical shutoff and audible / visual alarm. Additional built-in cabinet in the front to store accessories.

## Environment-Friendly

Spill containment meets the needs of AS1940:2017 to contain the contents of the primary tank. UL142 approved.

Gross Capacity: <b>11,500L</b>	Height: <b>1,284 mm</b>
Safe Fill: <b>10,350L</b>	Length: <b>5,750 mm</b>
Weight (Empty): <b>4,050 kg</b>	Width: <b>2,262 mm</b>
Weight (Full Tank): <b>12,744 kg</b>	Design Standards: <b>UL 142</b>
Australian Standards: <b>AS1940, AS1692</b>	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

### Standard Fittings

2" Open nozzle fill point, 2" pump suction pipe, 1" return port, 3" flanged suction point with internal anti-siphon valve and integrated thermal relief, internal bunding with pressure vent, air breather vent with gauze screen, calibrated fluid level dipstick, interstitial space dip point, manway access.

### Optional Packages

Complete transfer pump solution, water and particulate filter kits, fuel hose kits fitted with quick couplers.