

DATASHEET

# Fuelfix & Tanks2Go 2,000L Self-Bunded Tank

An on-site fuel solution for the direct supply of fuel to stationary equipment or the refuelling of fleet.

## Movable

Full load lifting eyes, forklift pockets and internal baffles are designed to allow safe and easy handling of the tank full of fuel.

## Stackable

Easily stackable design supports 2 high when full and 3 high when empty, reducing storage space requirements.

## Accessible

Access manway for thorough maintenance and inspection. Removable inner tank for servicing and cleaning.

## Efficient

Lockable cabinet secures equipment. Fuel ports can run up to 3 pieces of equipment.

## Environment-Friendly

Secondary containment is compliant with AS1940 (2017). The tank design is compliant with UL142.



Gross Capacity: <b>2,070L</b>	Height: <b>1,326 mm</b>
Safe-Fill: <b>2,007L</b>	Length: <b>2,256 mm</b>
Weight (Empty): <b>1,140 kg</b>	Width: <b>1,103 mm</b>
Weight (Full-Tank): <b>2,805 kg</b>	Design Standards: <b>UL142, ULC-S601-07.</b>
Australian Standards: <b>AS1940, AS1692</b>	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

### Standard Fittings

3" fill point, 6 x 1" suction/return ports, 1 x 1 1/4" suction line. Roll over vent.

### Optional Fittings

Complete transfer pump kits, water and particulate filter kits, fuel up to 2 feed and return blocks, fuel hose and quick couplers.