

Fuelfix & Tanks2Go 3,000L Self-Bunded Tank

Extend the run time of your diesel-powered equipment with our 3,000L tank. Increased efficiency and reduced costs mean maximized revenue.



Movable

Full load lifting eyes and forklift pockets and internal baffles are designed to allow safe and easy handling of the tank full of fuel.

Stackable

Easily stackable design supports 2 high when full and 3 high when empty, reducing storage space requirements.

Accessible

Access manway for thorough maintenance and inspection.

Efficient

Lockable cabinet secures equipment. Fuel ports can run up to 3 pieces of diesel-powered equipment.

Environment-Friendly

Secondary containment is compliant with AS1940 (2017). The tank design is compliant with UL142.

Gross Capacity: 3,130L	Height: 1,326 mm
Safe Fill: 3,000L	Length: 2,256 mm
Weight (Empty): 1,450kg	Width: 1,621 mm
Weight (Full Tank): 3,940 kg	Design Standards: UL142, ULC-S601-07
Australian Standards: AS1940, AS1692	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

3" fill point, 6 x 25NB suction/return speared lines, 1 x 32NB suction/return speared line, roll over vent.

Optional Fittings

Complete transfer pump kits, water and particulate filter kits, fuel up to 2 feed and return blocks, fuel hose and quick couplers.