

Fuelfix & Tanks2Go 4,000L Self-Bunded Tank

Extend the run time of your dieselpowered equipment with the self-bunded 4,000L tank. Increased efficiency with reduced expenses means maximized revenue.



Stackable

Easily stackable design supports 2 high when empty, reducing storage space requirements. (not rated to be stacked when full.)

Accessible

Access manway for thorough maintenance and inspection of the inner tank.

Efficient

Top mounted lockable spill containment box secures tank fill, dip point and interstitial dip point.

Renvironment-Friendly

Tank complies with UL142, ULC S-601-07 design.

Gross Capacity:	Height:
4,200L	1,306 mm
Safe Fill:	Length:
4,070L	2,256 mm
Weight (Empty):	Width:
1,800 kg	2,256 mm
Weight (Full Tank): 5,178 kg	Design Standards: UL142, ULC S-601-07
Australian Standards: AS1940, AS1692	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

3" fill point, 6 x 1" suction/return lines, 1 x 1 $\frac{1}{4}$ suction/return, roll over vent.

Optional Fittings

Complete transfer pump kits, water and particulate filter kits, fuel up to 2 feed and return blocks, generator hose kit with suction and return hoses fitted with quick couplers.





Call 1300 734 764 or visit fuelfix.com.au