

DATASHEET

# Fuelfix & Tanks2Go 500L Self-Bunded Tank

Ideal for use in stand-by applications for refuelling smaller equipment, such as industrial heaters, small generators, lighting towers and more.



## Movable

Full load lifting eyes, forklift pockets and internal baffles are designed to allow safe and easy handling of the tank full of fuel.

## Stackable

Easily stackable design supports 2 high when full and 3 high when empty, reducing storage space requirements.

## Accessible

Access manway for thorough maintenance and inspection. Removable inner tank for servicing and cleaning.

## Efficient

Lockable cabinet secures equipment. Fuel ports can run up to 3 pieces of diesel-powered equipment.

## Environment-Friendly

Secondary containment is compliant with AS1940 (2017). The tank design is compliant with UL142.

Gross Capacity: <b>500L</b>	Height: <b>855 mm</b>
Safe Fill: <b>474L</b>	Length: <b>1,165 mm</b>
Weight (Empty): <b>415 kg</b>	Width: <b>1,165 mm</b>
Weight (Full Tank): <b>889 kg</b>	Design Standards: <b>UL142, UN31A, UN1202</b>
Australian Standards: <b>AS1940 &amp; AS1692</b>	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

### Standard Fittings

3" fill point; 2" fusible link fill port, 1" pump feed with flexible suction line, strainer and non-return valve, 1 engine feed and return port set, working vent, breather vent.

### Optional Fittings

Complete transfer pump kits, water and particulate filter kits, fuel up to 2 feed and return blocks, fuel hose and quick couplers.