

# Fuelfix & Tanks2Go 6,500L Self-Bunded Tank

The Fuelfix Self-Bunded 6,500L is a compact, double-walled tank designed for stationary storage. Quick and easy set up and relocation of fuel where you need it, when you need it.

## Movable

The load lifting eyes and forklift pockets are designed to allow safe and easy handling of the tank when empty.

## Stackable

Easily stackable design supports 2 high when full and 3 high when empty, reducing storage space requirements.

## Accessible

Access manway for thorough maintenance and inspection of inner tank.

## Efficient

Lockable equipment cabinet to secure equipment and ports to run multiple pieces of equipment.

## Environment-Friendly

Spill containment meets the needs of AS1940:2017 to contain the contents of the primary tank. UL142 approved.



Gross Capacity: <b>6,240L</b>	Height: <b>1,326 mm</b>
Safe Fill: <b>6,050L</b>	Length: <b>3,319 mm</b>
Weight (Empty): <b>2,420 kg</b>	Width: <b>2,246 mm</b>
Weight (Full Tank): <b>7,441 kg</b>	Design Standards: <b>UL 142</b>
Australian Standards: <b>AS1940, AS1692</b>	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

### Standard Fittings

3" fill line, 6 x 1" pump suction pipes, 1" & 1<sup>1/4</sup>" suction pipes set up for pump mounting, roll-over vent, internal bunding with pressure vent, air breather vent with gauze screen, calibrated fluid level dipstick, interstitial space dip point and static vent.

### Optional Fittings

Complete transfer pump solution, water and particulate filter kits, fuel up to 2 feed and return blocks, fuel hose kits fitted with quick couplers.