

# Fuelfix & Tanks2Go

## DC 70,000L Self-Bunded Tank

This dual compartment tank has separate diesel and AdBlue compartments. The AdBlue compartment is made from high quality stainless steel and is insulated for hazardous chemical storage while the diesel tank is made from carbon steel. This tank is designed to leverage the efficiencies of storing diesel and AdBlue together. Ideal for transportation depots, mining and construction on-site refuelling.



### Movable

This tank is easily transported using side-loaders, removing the need for cranes, EWP's and any related working at height risks when loading and unloading.

### Accessible

Permanent ladder and platform complete with kickboards in accordance with AS1657 for ease of inspection and access, the ladder can be fitted to either side of the tank. Design enables undertank visibility and all key tank nozzles for both products are accessible from the front-end of tank.

### Secure and Efficient

Self-bunded design with an insulated stainless-steel compartment is suitable for storage of AdBlue and other chemicals with specialized storage requirements. The outside of the tank is finished in marine grade polyurethane white paint. The front mounted security doors have container lock handles to secure the fuel and pumping equipment.

### Environment-Friendly

Pump bay housing with spill containment as well as double wall separation of AdBlue and diesel to prevent contamination in the event of a leak. Both tanks feature an internal overfill prevention and anti-siphon valves.

Gross Capacity: <b>67,650L</b>	Height: <b>2,896 mm</b>
Safe Fill: <b>60,200L (Diesel); 5,000L (AdBlue)</b>	Length: <b>12,180 mm</b>
Weight (Empty): <b>13,660 kg</b>	Width: <b>2,430 mm</b>
Weight (Full Tank): <b>69,693 kg</b>	Design Standards: <b>UL 142, ULCS601</b>
Australian Standards: <b>AS1940, AS1657, AS1692</b>	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

### Standard Fittings

3" Male camlock couplings with dust caps fitted to tanker filling points, wafer non-returns fitted to filling lines, 3" fire safe ball valves, container corner castings, primary tank access manway, calibrated fluid level dipstick and statutory signage and interstitial space dip points.

### Optional Packages

- HV/LV dispensing package
- Single or dual vehicle pump package (light to medium vehicles)
- AdBlue dispensing package
- Lubricant dispensing package
- Fuelfix fuel management system