

Fuelfix & Tanks2Go Solar-Powered Self-Bunded Fuel Trailer

Adding a solar panel and 12V pump to our fuel trailer takes this popular workhorse of the Fuelfix & Tanks2Go range to another level. Fuel dispensing is rated up to 60L per minute through a solar powered pumping unit.

Generating 80W with a 20-hour battery life, this solar option is emission free, low noise, self priming, and virtually maintenance free. With the built-in safety features, the stringent safety requirements of many sites are easily met.

Efficient

A large capacity storage battery provides enough energy for 170 minutes of operation without recharging the battery. A 50A Anderson plug connection is also provided for easy connection to external power sources. The design of the mobile fuel trailer delivers low operating noise, zero emissions and a virtually maintenance free user experience.

Safe

The dual axle construction makes the fuel trailer well balanced and easy to tow, even when fully loaded. It has an excellent ground clearance yet retains a low centre of gravity. All required signage, LED taillights and reflective tape are installed (on request).

Environment-Friendly

The bunded front containment area under the pump housing further reduces any risk of accidental spillage seeping into the ground.



Safe Fill: 1,200L	Height: 1,951 mm
Weight (Empty): 1,170 kg	Length: 4,793 mm
Weight (Full Tank): GTM: 2,000 kg	Width: 1,953 mm

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

Top-mounted 12 V solar panel. Heavy duty tyres on standard 16" rims with spare tyre, fluid level dipstick, flashing refuelling light, LED charge indicators, emergency stop button with battery isolation switch, 10m x 25mm diameter retractable hose reel with auto shut-off nozzle, fuel meter, disc brakes with manual handbrake, jockey wheel with swivel retraction for optimum ground clearance, 50mm tow hitch, 20mm generator connection points, 2 safety chains with load-rated shackles, 2" dip point with camlock, 3" fill and vent point with camlock, standard round 7-pin trailer plug, 9 kg dry powder fire extinguisher, statutory signage, 32L spill kit, wheel chocks.

32L Spill Kit in top mounted tuff box includes:

- 2 x 1m miniboom to contain and absorb fuel spills
- 1 x pack of absorbent 300 x 300 pads
- Absorbent powder which holds 11 times own weight
- Protective gloves
- Bags for contaminated material to allow for safe disposal