

Fuelfix & Tanks2Go 110,000L Self-Bunded Tank

Experience the proven efficiency of the Fuelfix 110,000L self-bunded tank. This fuel storage solution provides a large storage capacity and includes an unloading pump to keep your fuel delivery costs down. Everything is pre-wired to ensure rapid deployment.



Movable

Safe handling can be easily achieved using a crane and flat deck.

Accessible

Access manway for thorough maintenance and inspection of the primary tank.

Efficient

The front cowling area is self-bunded and can be fitted with a removable skid pump module or day tank.

Environment-Friendly

Self-bunded tank constructed to AS1692 and AS1940. The front cowling ensures that any spills that occur during tank filling or maintenance are securely contained within a bunded area.

Capacity: 115,745L	Height: 4,150 mm
Safe Fill: 110,000L	Length: 14,684 mm
Weight (Empty): 20,100 kg	Diameter: 3,502 mm
Weight (Full Tank): 110,720 kg	Australian Standards: AS1940, AS1692, AS1657

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

9 kg dry powder extinguisher, vent pipe and dipstick, 80mm fill line with mechanical overfill prevention valve, unloading pump, 80 mm suction line with anti-syphon valve, 2" wet test port, audible overfill alarm and cowling light, ladder, ladder cage (where applicable) and platform built to AS1657

Optional Equipment

- Various electric and diesel-powered dispensing and tanker unloading solutions to suit all applications
- Fuelfix fuel management system with optional tank gauging
- 1,000L or 2,000L generator day tank
- NMI approved meter