

DATASHEET

Fuelfix & Tanks2Go 27,000L Self-Bunded Tank

The 27,000L fuel tank (T30) has superior capacity but is narrow enough to fit where space is limited. Easy to position on site and with an electric or diesel powered HV/LV skid pump module, refuelling your fleet couldn't be easier.

Movable

Safe handling can be easily achieved using a crane or tilt-tray.

Accessible

Access manway for thorough maintenance and inspection of the primary tank.

Efficient

The front cowling area is self-bunded and can be fitted with a removable skid pump module or day tank.

Environment-Friendly

Self-bunded tank constructed to AS1692 and AS1940. The front cowling ensures any spills are securely contained within the bunded area.



Capacity: 27,600L	Height: 2,900 mm
Safe Fill: 26,600L	Length: 9,800 mm
Weight (Empty): 8,000 kg	Diameter: 2,250 mm
Weight (Full Tank): 30,344 kg	Design Standards: AS1692, AS1657
Australian Standards: AS1940, AS1692, AS1657	

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

9 kg dry powder extinguisher, vent pipe and dipstick, 80mm fill line with mechanical overfill prevention valve, 50 mm suction line, 2" wet test port, audible overfill alarm and cowling light. Ladder, ladder cage (where applicable) and platform built to AS1657

Optional Equipment

- Various electric and diesel-powered dispensing and tanker unloading solutions to suit all applications
- Fuelfix fuel management system with optional tank gauging
- 1,000L generator day tank
- NMI approved meter